

Brought to you by [sewingideas.com](http://sewingideas.com)



## Beauty Cache



### Shopping List:

- |  |  |   |
|--|--|---|
| <input type="checkbox"/> Edge Joining Foot #412280245              | <input type="checkbox"/> Pressing board/mat                                      | <input type="checkbox"/> Huskystar ER 10 Needle Felting Machine       |
| <input type="checkbox"/> Left Edge Topstitching Foot #412784245    | <input type="checkbox"/> 1/3 yd of colorful cotton fabric for lining and pockets | <input type="checkbox"/> Roving                                       |
| <input type="checkbox"/> Edge Stitching Foot #412407701            | <input type="checkbox"/> 1/3 yd Silk Dupioni                                     | <input type="checkbox"/> Robison Anton 40 wt. Rayon Embroidery Thread |
| <input type="checkbox"/> Sewing machine needles                    | <input type="checkbox"/> 13" x 18" Warm and Natural Cotton Batting               | <b>From cotton cut:</b>   |
| <input type="checkbox"/> Water soluble pen or chalk marking pencil | <input type="checkbox"/> Single sided 14" zipper                                 | <input type="checkbox"/> One 11" x 16" rectangle                      |
| <input type="checkbox"/> Magnetic Pin Bowl 6" diameter #140001501  | <input type="checkbox"/> Husqvarna Viking Piping Foot #411851045                 | <input type="checkbox"/> One 11" x 11" square                         |
| <input type="checkbox"/> Seam ripper #140000165                    | <input type="checkbox"/> Twin Needle size 2.0                                    | <b>From the silk dupioni cut:</b>                                     |
| <input type="checkbox"/> Buttonhole Knife Set #2020                |  | <input type="checkbox"/> One 13" x 18" rectangle                      |

## Make the outside fabric:

1. Layer the batting and the silk dupioni, wrong sides together.
2. Using a 2.0/80 twin needle and two spools of RA, sew a grid of 2" squares over the entire piece of batting and silk dupioni.
3. Use the Huskystar ER10 to attach small pieces of roving in the center of selected squares.
4. Program the desired name into the Husqvarna Viking Sapphire and stitch it out onto the silk dupioni.
5. Square up the batting/dupioni piece to be 11"x16". Finish all four edges with a three step zig zag.

## Construct the Bag:

All seam allowances are approximately ½" (10 mm line on the throat plate).

*Helpful hint:* Backstitching 2-3 stitches at the beginning and end of all seams is the best way to keep the seams strong and stop them from unraveling. Or use the FIX feature on your Husqvarna Viking sewing machine.

1. Lay the quilted dupioni on a flat surface so that the batting side is face up. Place the rectangle of cotton fabric over the quilted dupioni with the wrong side against the batting; align the cut edges. Use straight pins to secure the two fabrics together along the edges.
2. To prepare the pocket, fold the fabric square in half and sew two adjacent sides.
3. Trim off the corner leaving a 1/8" seam allowance.
4. Turn the pocket right side out. Press the seams out.
5. Take the short finished end of the pocket and turn it up 4"-5". Sew along both side edges. Do not sew over pins! Instead remove them as the presser foot approaches them.
6. With the back of the pocket facing the cotton lining, center the pocket over one of the 11" sides of the fabric and quilted dupioni rectangle. Pin in place.
7. Snap on the piping foot. (A Pearls 'n Piping Foot can be used in place of a piping foot.) Unzip the zipper. Over an 11" side, lay the right side of the zipper over the right side of the fabric. To ensure the zipper is in the right place, the zipper tape should be lined up with the cut edge of the fabric and quilted dupioni. The suggested zipper length is longer than the width of the bag. Approximately 1 1/2" of the zipper should be extending beyond each edge of the bag. Lower the piping foot over the zipper with the channel of the foot over the coil of the zipper. Sew the zipper to the edge of the bag.
8. Zip up the zipper. Bring the other side of the zipper tape over the opposite 11" side. Pin the zipper tape to the opposite side, lining up the side seams. Carefully unzip the zipper. Lower the channel of the piping foot over the coil of the zipper. Sew the zipper to the bag.
9. Zip the zipper so the zipper pull is halfway between the edges of the fabric.
10. Pin the edges of the bag, turning the zipper tapes toward the bag. Sew the side seams.
11. As you sew over the zipper, sew slowly and make sure to backstitch. Once the seam is sewn, cut the portion of the zipper that is extending beyond the seam allowance.
12. To give the bag a squared bottom, unzip the zipper the rest of the way. Poke your fingers in the bottom corners of the bag, smoothing out the fabric. Fold the bag with the bottom fold matching the side seam making a point on the inside. Pin. Using a water soluble marking pen, draw a line 2" away from the point. Sew over the line. Repeat for the other side.
13. Turn the bag right side out. Fill it with your personals and you're ready to go.